小身材 大能力 打造功率密度新高度

P H

	M6-	-L4-P	3550	4000	4500	5000	5600	6300	7100	
		[kW]	355	400	450	500	560	630	710	
	[kVA] 1		443	520	568	630	755	790	840	
	[A] ²		640	750	820	910	1090	1140	1250	
		3		120%-1min						
				0.05 240Hz 0.05 60Hz						
		4	3Ø 380V 460V							
		3Ø 380V 460V 50/60Hz								
			-15% +10% ± 5%					3%		
			1% 1%							
		[kVA] ⁵	407	477	521	578	693	725	795	
	[A]	6	587	688	752	835	1000	1046	1147	
		IP20								
				200kg 300k		Okg	g 440kg			
					PWM		1k 6kF	łz ⁷		
DC										

M6L4-H	3150	3550	4000	4500	5000	5600	6300	
[kW]	315	355	400	450	500	560	630	
[kVA] 1	409	443	520	568	658	755	790	
[A] ²	590	640	750	820	950	1090	1140	
3		150%-1			min 200%-3sec			
		0.05 40	00Hz	0.	.05 60H	łz		
4	3Ø 3			380V 460V				
		;	3Ø 380V	460V	50/60Hz	7		
	-15% +10%		± 5%	3%				
		1%	1%					
[kVA] ⁵	375	407	477	521	604	693	725	
[A] ⁶	541	587	688	752	872	1000	1046	
	IP20							
	20	200kg		300kg		440kg		
			PWM		1k 8kF	łz ⁷		
DC								

1 400V 2 AC400V 3 10 1 4

			/ / V/f						
		PG	0.05Hz 240Hz 1 1000/50Hz ⁵						
		PG	0.25Hz 240Hz 1 200/50Hz ⁵						
1		PG	250rad/sec ± 0.01%						
	/	PG	100rad/sec ± 0.5%						
		PG	1:50						
		PG	1:20						
		PG	± 10%						
		PG	± 20%						
			0.01Hz						
			0.05% 12bit 0 10V 4 20mA 0.1% 11bit 0 5V						
			± 0.01% -10 40						
			± 0.2% 25± 10 ²						
	PG		24V 491.52kHz ³						
			0.05 20Hz 0.1~10 1 10						
		,							
	l	l							
			<u> </u>						